



ECO800[™] VARIABLE SPEED POOL PUMP

The Energy Saver

FEATURES & BENEFITS

The Onga Eco800 is the ideal pump for new or existing pools. Utilising advanced hydraulic design and the latest technology in permanent magnet, variable speed motors, the Onga Eco800 has the perfect combination of efficiency and performance. The Onga Eco800 delivers energy savings and the power when you need it. You will also have the peace of mind that you are doing your bit for the environment and reducing your carbon foot print.

Variable speed pump, with 3 programmable speeds, allows you to effortlessly select the most efficient setting to meet your filtration, cleaning and water feature needs.

A specially designed sounddampening pump casing and base make pump operation incredibly quiet.

Variable Speed with 3 Programmable Settings Axial flux, brushless, permanent magnet motor delivers high efficiency and low noise levels.

The Cam and Ramp[™] lid is easy to remove and locks in place with a quarter turn, making inspection and cleaning a breeze.

The high-capacity trap holds a large amount of debris, so you clean less often.

Quick-disconnect plumbing unions.

Fault protected motor prevents damage by automatically shutting down the motor in the event of a locked rotor, under voltage, over voltage or over current condition and will automatically reduce the speed during an over temperature condition.

Constructed of our durable, thermoplastic, composite resin, so you can be sure it will stand up to the harshest conditions. **P**recision-fit internal components and superior hydraulic design deliver effortless performance, energy savings and extended pump life.

ec


A heavy-duty construction and a motor rated for continuous operation make the Eco800 a tough, long-lasting performer.

8 star energy rating.

VARIABLE SPEED WITH 3 PROGRAMMABLE SETTINGS

The Onga Eco800 uses an axial-flux, brushless, DC motor which offers high efficiency levels compared with conventional induction motors. Combined with the latest in electronic control, this allows the motor/pump to run at varying speeds.

> • The multiple speeds offered by the Eco800 enable the pump to run slower and consume less energy but still have the ability to run at full speed if required by the application.





EC0800 VARIABLE SPEED POOL PUMP

ΡΙΙΜΡ ΠΔΤΔ

POMP DATA	Low	Medium	High	
RPM*	1450	2400	2800	
Motor Input Power (P1) (max)	160W	595W	940W	
Motor Output Power (P2) (max)	130W	475W	750W	
Current (max)	1.3A	4.4A	6.5A	
Sound Power Level (Lwa)	57.5 dB	65.2 dB	69.3 dB	
Maximum Rating	2850RPM, F	2850RPM, P1 975W, P2 800W, 6.7A		
Voltage	230-240VAC	230-240VAC 50Hz Single Phase		
Motor type	800W BLDC	800W BLDC TEFC		
Ingress Protection	IPX5	IPX5		
Inlet connection	ABS Barrel	ABS Barrel Union to suit 50mm PVC		
	pressure pi	pressure pipe		
Outlet Connection	ABS Barrel	ABS Barrel Union to suit 50mm PVC		
	pressure pi	ре		
Maximum Water Temperature:	40°C	40°C		
Maximum Ambient Temperature:	55°C	55°C		
*4	14			



MATERIAL SPECIFICATIONS

Pump Casi Impeller

Clamp Ring Casing O

Lid O - Ring Barrel Unic Barrel Unic

Base Diffuser 0

Motor Supply Cor Bearings

Diffuser

ng	Polypropylene 40% Glass Filled
	Polyphenylene Ether
	Polypropylene 40% Glass Filled
	Polystyrene
	Polycarbonate
	Polypropylene 20% Glass Filled
Ring	Nitrile
	Polypropylene
- Ring	Nitrile
	Nitrile
ns	PVC
n O – Ring	Nitrile
Seal	³ / ₄ " Type 6 Carbon - Ceramic, S/S, Nitrile
	Aluminium Alloy
ł	H07RNF 3G 1mm, 2m
	6302, 6303

В 179mm 256mm 354mm IT 0


272

DIMENSIONS

637mm







AVAILABLE FROM:



Head Office		New Zealand	
Pentair AU/NZ:	1-21 Monash Drive,	National Customer Service:	Phone: 0800 654 112
Dandenong South, Vic 3175			Fax: 0800 806 642
Australia		National Dealer Locator:	Phone: 0800 664 269
National Customer Service: National Dealer Locator:	Phone: 1300 137 344 Fax: 1800 006 688 Phone: 1800 664 266	Email: Web:	nz.sales@pentair.com www.pentair.co.nz
National Dealer Educator.	1110116. 1000 004 200	International Australia/New Zealand	
Email:	au.sales@pentair.com	PI	none: +61 3 9709 5800
Web:	www.pentair.com.au	Fa	ax: +61 3 9709 5888

L300213 A1112

Display, publication, modification or distribution is strictly prohibited without the prior written permission of Pentair Water Pty Ltd.

Disclaimer: Every endeavour has been made to publish the correct details in this publication. No responsibility will be taken for errors, omissions or changes in product specifications. Pentair reserves the right to change specifications. pumps / filters / heaters / heat pumps / automation / lighting / cleaners / sanitizers / water features / maintenance products